



Architectural/Engineering Specification:

Polished chrome-plated widespread with adjustable centers from 6"[152mm] to 20"[508mm], a 8"[203mm] bent riser spout and quarter turn ceramic disc cartridges. Unit is furnished with a 2.2 GPM [8.3 L] pressure compensating aerator (complying with ANSI A112.18.1 Standard for flow), 4" [102mm] vandal-resistant color-coded metal wrist blade handles, mounting hardware and 1/2" NPSM coupling nuts for standard lavatory risers. Widespread accommodates installations up to 1-1/8" [29mm] thick.

Zurn Lead Free products (-XL) is the line of durable, high quality brass faucets and fixtures that are designed and manufactured to comply with Section 1417 of the Safe Drinking Water Act (SDWA) which mandates the weighted average lead content of no more than 0.25% of the wetted surface.

Compliance and Certification:

- Complies with ASME A112.18.1/CSA B125.1
- Lead Free Compliant
- ADA Compliant



Aerator Options:

	Flow rate GPM [LpM]	Vandal Resistant	Pressure Compression	Outlet Type
-2M	2.2[8.3]	✓	✓	Aerator
-3M	0.5[1.9]	✓	✓	Spray
-4M	2.2[8.3]	✓	✓	Laminar
-5M	2.0[7.6]			Spray
-7M	1.0[3.8]		✓	Spray
-14M	2.5[9.5]	✓		Aerator
-16M	1.0[3.8]	✓	✓	Spray
-17M	1.5[5.7]	✓	✓	Aerator
-18M	1.5[5.7]	✓	✓	Laminar
-19M	1.5[5.7]		✓	Laminar
-20M	1.0[3.8]	✓	✓	Laminar
-21M	1.0[3.8]			Laminar
-22M	1.0[3.8]	✓		Laminar

Suffix Options:

- CWO Cold Water Only
- FC 2.0 GPM [7.6L] Laminar Flow Control in Base of Spout
- G 1-1/4" [32mm] Grid Strainer Drain
- HS Hose and Spray
- ICT Inter-connecting Copper Supply Tubes for 8" In-line Centers
- P 1-1/4"[32mm] Pop-up Drain

Architectural/Engineering Approval

The information contained in this document is subject to change without notice.
Please contact Zurn for most up to date information.

Rough-in dimensions/Overview dimensions

