

 $7\frac{15}{16}[201]$

Note: All dimensions are for reference only. Do not use for pre-plumbing.

6[152]

OPTIONAL ACCESSORIES

Suffix	Description
FC	2.0 GPM [7.6 L] Laminar Flow Control in Base of Spout
G	1-1/4" [32mm] Grid Strainer Drain
HCT	Hot/Cold Text Indexes
P	1-1/4" [32mm] Pop-up Drain
-PT	1-1/4" [32mm] Cast Brass P-Trap with a 7-1/2" [191mm] Long 17-Gauge Wall Bend
2F	2.2 GPM [8.3 L] Vandal-Resistant Pressure Compensating Female Aerator
3F	0.5 GPM [1.9 L] Vandal-Resistant Pressure Compensating Female Aerator
4F	2.2 GPM [8.3 L] Vandal-Resistant Pressure Compensating Female Laminar Flow
5F	2.0 GPM [7.6 L] Female Spray Outlet
7F	1.0 GPM [3.8 L] Pressure Compensating Female Spray Outlet
16F	1.0 GPM [3.8 L] Vandal-Resistant Pressure Compensating Female Spray Outlet
17F	1.5 GPM [5.7 L] Vandal-Resistant Pressure Compensating Female Aerator
18F	1.5 GPM [5.7 L] Vandal-Resistant Pressure Compensating Female Laminar Flow

ZURN INDUSTRIES, INC. ♦ COMMERCIAL BRASS OPERATION ♦ 2640 SOUTH WORK STREET ♦ FALCONER NY 14733 Phone: 1-716-665-1132 ♦ Fax: 1-716-665-1135 ♦ World Wide Web: www.zurn.com